

Product Code: BCT52-26 17-173

52Kg Blast Chiller/Freezer Cabinet



Features & Benefits

- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- Freezing capacity from +70°C to -18°C in less than 240 minutes within specifications
- Dedicated 52Kg blast chiller with occasional 26Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior and interior the 'gold standard' in performance finishes
- Intuitive touch control panel – just press and go!
- 14 Shelf Positions for GN 1/1 Pans

External Finish

304 s/s Standard

Base Fittings

Castors 80mm Standard

Legs 150mm Option

Electrical, Service & Ecodesign Data

230/1/50 Standard

Fuse Required (A) 16

Internal Finish

304 s/s Standard

Doors

Solid Standard

Left Hand Hinged Door Option

Product Extras

Hold Facility Standard

Shelving

Gastronorm Pans Option

Nylon Coated Shelf Option

Additional S/S Trayslides Standard

GN1/1 Shelf Standard

Refrigeration

R404a - Industry Standard Standard

Integral Refrigeration System Standard

Less Condensing Unit Option

Remote Refrigeration System Option

Specification

Width 755

Height 1805

Depth 690

Weight (Packed, kg) 176

Chilling Capacity (Kgs) 52

Freezing Capacity (Kgs) 26

Gross Volume 52

RS485 connection for HACCP data logging Option

Noise dBA @ 1m TBC

Footnotes

- Chilling Capacity: 52KG. Freezing capacity: 26KG 70°C to 3°C in less than 90 minutes within specifications, entry temperature up to 90°C for chilling
- Please add 55mm to depth for spacer



Energy



Quality



Value



Design



Hygiene



After Care



Regethermic | Unit 4, 7-9 Orion Rd, Lane Cove West, NSW, 2066, Australia
Tel. +61 2 9966 9500 | www.regethermic.com.au | info@regethermic.com.au



We reserve the right to make changes without notice.