



Technical Data

Dimensions (WDH): 1550 x 1330 x 2350
 Clear door opening: 895 x 1898
 Trolley capacity: 890 x 1040 x 1890
 Floor: 25mm floor available (not standard)

Temperature (chilling): 70°C to 3°C in less than 90 mins
 Temperature (freezing): 70°C to -18°C in less than 240 mins
 Capacity: 150kg

Cooling Duty @ -30°C (kW): 9
 Number of fans: 3
 Number of coils: 1
 Fan load (kW): 0.6
 Defrost load (kW): 4
 Drainage: 22mm drain connection / tundish required
 Evaporating temperature: -30°C
 Refrigerant control: TEV (MOP @ +0°C)
 Gas: R404a
 Inlet size: 1/2"
 Outlet size: 1 1/8"
 Electrical supply: 240V 20A (fans and defrost)



Notes:

- Modular unit / Assembly required
- Floor surface +/- 5mm recommended
- Separate 415V 3 phase compressor and condenser unit required. Available on request
- Right hand hinged, left hand hinged and pass through models shown
- Pass through models available in various door hinging arrangements LH/LH, RH/RH, RH/LH, LH/RH



Regethermic | Unit 4, 7-9 Orion Rd, Lane Cove West, NSW, 2066, Australia
 Tel. +61 2 9966 9500 | www.regethermic.com.au | info@regethermic.com.au



We reserve the right to make changes without notice.