



**Technical Data**

Dimensions (WDH):	1550 x 1330 x 2350
Clear door opening:	895 x 1898
Trolley capacity:	890 x 1040 x 1890
Floor:	25mm floor available (not standard)
Temperature (chilling):	70°C to 3°C in less than 90 mins
Capacity:	150kg
Cooling Duty @ -15°C (kW):	11.5
Number of fans:	3
Number of coils:	1
Fan load (kW):	0.6
Defrost load (kW):	0
Drainage:	22mm drain connection / tundish required
Evaporating temperature:	-15°C
Refrigerant control:	TEV (MOP @ +15°C)
Gas:	R404a
Inlet size:	1/2"
Outlet size:	1 1/8"
Electrical supply:	240V 20A (fans and defrost)



**Notes:**

- Modular unit / Assembly required
- Floor surface +/- 5mm recommended
- Separate 415V 3 phase compressor and condenser unit required.
- Right hand hinged, left hand hinged and pass through models shown
- Pass through models available in various door hinging arrangements

Available on request

LH/LH, RH/RH, RH/LH, LH/RH



Regethermic | Unit 4, 7-9 Orion Rd, Lane Cove West, NSW, 2066, Australia  
 Tel. +61 2 9966 9500 | www.regethermic.com.au | info@regethermic.com.au



We reserve the right to make changes without notice.