

Product Code: RBCT20-60 17-118

Roll-In Blast Chiller Cabinet (Integral Refrigeration System)



Features & Benefits

- Specific model to accept the Rational 201 trolley with a chilling capacity of 60kgs
- Chilling capacity 90°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- For ventilation and service access ensure that 400mm minimum clearance is allowed above the unit
- RBCT20-60 is supplied with an integral condensing unit, RBCT20-60R as a remote unit
- RBCT20-60 R Twin compressor condensing unit option supplied housed and dressed for specific applications

External Finish		Internal Finish		Shelving	
304 s/s	Standard	304 s/s	Standard	Additional S/S Trayslides	Standard
Doors		Refrigeration		Electrical, Service & Ecodesign Data	
Solid	Standard	R404a - Industry Standard	Standard		
Left Hand Hinged Door	Option	Drain Rqd	1 1/2 BSP	400/50/3	Standard
Product Extras		Integral Refrigeration System	Standard	Fuse Required	
		Less Condensing Unit	Option	16	
Hold Facility		Remote Refrigeration System	Standard		
		Specification			
		Dimensions (Width)	980		
		Dimensions (Height)	2190		
		Dimensions (Depth)	865		
		Weight (Unpacked, kg)	281		
		Weight (Packed, kg)	314.57		
		Chilling Capacity (Kgs)	60		
		Gross Volume	60		
		RS485 connection for HACCP data logging	Option		
		Noise DbA @ 1M	TBC		

Footnotes

- Requires connection to external drain. 1x 1/2" BSP Drain outlet
- Chilling Capacity - 60 KG. Chilling capacity 90 degrees C to 3 degrees C in less than 90 minutes within specifications. Entry temperature of up to 90 degrees C for chilling.
- Dimensions: For ventilation and service access ensure that 400mm minimum clearance is allowed above the RBC 20-60
- Maximum Ambient 43 degrees C








Energy

Quality

Value

Design

Hygiene

After Care

